

Pressure Area Care | **ATTIVO™** Seating Systems

The ATTIVO seating systems offer a choice of dual-powered cushions to provide pressure relief and reduced interface pressures for all patient types within all care environments.



Power Unit	
Length	210mm
Height	105mm
Depth	205mm
Weight	2.2kg
Alternating Cycle Time	16 mins
DC Input Voltage	15V Nominal
Fixed Internal Battery	6V 2.5Ah NiMH

Power Adapter	
Mains Adapter Type	FW7362M/15 (supplied)
Input	100-240V / 50-60Hz / 700mA
Output	15V cc / 2A
Cable Length	4 metres

Cushions	B.A.S.E.® SEQUENTIAL	B.A.S.E.® RECLINER MAT
Length	430mm	1080mm
Width	430mm	430mm
Depth	70mm	70mm
Weight	1.9kg	3.9kg
Inner Construction Materials	PVC bellows within punched CMHR foam surround	PVC bellows within punched CMHR foam surround
Cover Material	PU coated stretch nylon	PU coated stretch nylon
Number of Cells	48	120
Max. User Weight	127kg / 20 stone	127kg / 20 stone
Min. User Weight	None	None

Covers are anti-bacterial/microbial treated (active ingredient: zinc pyrithione)

ATTIVO and B.A.S.E. are Trade Mark of Talley Group Limited.

Talley products are manufactured to comply with BSI, IEC, UL and other European safety standards. Talley design and manufacture products to conform to the requirements of ISO9001, ISO13485 and Directive 93/42/EEC. Every care has been taken to ensure that the information contained in this brochure was correct at the time of going to press. However, Talley reserve the right to modify the specification of any product without prior notice in line with a policy of continual product development. Our standard terms and conditions apply. © Talley Group Limited 2016. All rights reserved.

